



Tabela rozładowań stałym prądem A500 dla 20°C

Prąd rozładowania w [A] do 1,85 V/ogniwo										Prąd rozładowania w [A] do 1,80 V/ogniwo								
Typ	5'	10'	20'	30'	1 h	3h	5h	8h	10h	5'	10'	20'	30'	1 h	3h	5h	8h	10h
A502/10S	30,00	22,00	15,00	11,20	6,40	2,80	1,80	1,18	0,96	33,00	24,00	16,00	11,90	6,80	2,90	1,90	1,23	1,00
A504/3,5S	9,50	6,70	4,50	3,40	2,10	0,95	0,60	0,39	0,32	10,60	7,40	4,90	3,70	2,20	0,98	0,62	0,40	0,33
A506/1,2S	3,52	2,44	1,58	1,20	0,75	0,34	0,21	0,13	0,10	3,92	2,67	1,69	1,26	0,77	0,35	0,21	0,13	0,10
A506/3,5S	9,50	6,70	4,50	3,40	2,10	0,95	0,60	0,39	0,32	10,60	7,40	4,90	3,70	2,20	0,98	0,62	0,40	0,33
A506/4,2S	9,90	6,30	4,20	3,40	2,40	1,22	0,75	0,49	0,39	11,70	6,70	4,40	3,40	2,40	1,24	0,77	0,50	0,40
A506/6,5S	17,00	12,00	8,10	6,10	3,60	1,50	1,10	0,73	0,61	19,00	13,00	8,80	6,50	3,80	1,60	1,10	0,75	0,63
A506/10S	30,00	22,00	15,00	11,20	6,40	2,80	1,80	1,18	0,96	33,00	24,00	16,00	11,90	6,80	2,90	1,90	1,23	1,00
A508/3,5S	9,50	6,70	4,50	3,40	2,10	0,95	0,60	0,39	0,3	10,60	7,40	4,90	3,70	2,20	0,98	0,62	0,40	0,33
A512/1,2S	3,52	2,44	1,58	1,20	0,75	0,34	0,21	0,13	0,10	3,92	2,67	1,69	1,26	0,77	0,35	0,21	0,13	0,10
A512/2S	5,40	3,70	2,60	2,00	1,50	0,56	0,34	0,22	0,18	6,20	4,20	2,80	2,10	1,50	0,58	0,36	0,23	0,19
A512/3,5S	9,50	6,70	4,50	3,40	2,10	0,95	0,60	0,39	0,32	10,60	7,40	4,90	3,70	2,20	0,98	0,62	0,40	0,33
A512/6,5S	17,00	12,00	8,10	6,10	3,60	1,50	1,10	0,73	0,61	19,00	13,00	8,80	6,50	3,80	1,60	1,10	0,75	0,63
A512/10S	30,00	22,00	15,00	11,20	6,40	2,80	1,80	1,18	0,96	33,00	24,00	16,00	11,90	6,80	2,90	1,90	1,23	1,00
A512/16G5	40,00	29,00	20,0	15,0	9,8	4,3	2,7	1,8	1,4	47,0	33,0	22,0	16,0	10,2	4,4	2,8	1,8	1,5
A512/25G5	41,10	36,20	24,8	20,5	13,1	5,8	3,9	2,5	2,1	46,1	38,8	27,0	21,3	13,8	6,0	4,0	2,6	2,2
A512/30G6	60,70	49,30	36,5	28,0	18,0	7,6	4,9	3,2	2,6	75,5	54,8	39,9	30,0	19,1	7,9	5,1	3,3	2,7
A512/40A	75,00	63,00	42,0	34,0	22,0	8,8	6,4	4,3	3,5	86,0	69,0	47,0	36,0	23,0	9,2	6,7	4,4	3,6
A512/40G6	75,00	63,00	42,0	34,0	22,0	8,8	6,4	4,3	3,5	86,0	69,0	47,0	36,0	23,0	9,2	6,7	4,4	3,6
A512/55A	99,20	83,10	59,1	46,4	32,7	13,6	9,0	6,0	4,9	114,9	89,8	65,3	50,2	34,2	14,0	9,2	6,1	5,0
A512/60A	122,8	100,8	69,2	54,2	33,8	15,3	9,9	6,6	5,4	145,8	108,9	75,9	58,1	35,5	15,8	10,3	6,8	5,6
A512/60G6	122,8	100,8	69,2	54,2	33,8	15,3	9,9	6,6	5,4	145,8	108,9	75,9	58,1	35,5	15,8	10,3	6,8	5,6
A512/65A	95,80	83,1	65,8	56,4	35,8	16,6	11,0	7,4	6,1	120,8	100,3	75,4	60,4	38,6	17,4	11,5	7,5	6,2
A512/65G6	95,80	83,1	65,8	56,4	35,8	16,6	11,0	7,4	6,1	120,8	100,3	75,4	60,4	38,6	17,4	11,5	7,5	6,2
A512/85A	168,0	141,0	100,0	78,0	53,0	22,0	14,2	9,4	7,7	193,0	154,0	112,0	85,0	56,0	23,0	14,7	9,8	8,0
A512/115A	210,0	179,0	128,0	100,0	60,0	26,0	18,0	12,0	10,1	244,0	192,0	140,0	107,0	64,0	27,0	18,0	13,0	10,4
A512/120A	257,0	201,0	135,0	104,0	65,5	27,8	18,1	11,9	9,8	293,0	221,0	147,0	112,0	69,5	28,9	18,6	12,3	10,2
A512/140A	275,0	220,0	151,0	118,0	75,1	32,5	21,3	14,0	11,5	315,0	244,0	166,0	128,0	79,7	33,8	22,0	14,5	11,9
A512/200A	329,0	274,0	196,0	160,0	104,0	46,6	31,0	20,4	16,7	381,0	313,0	222,0	176,0	110,0	48,5	32,0	21,1	17,3

Gwarantujemy zasilanie.etc

ETC Plus SA
 ul. Drukarska 14
 27-400 Ostrowiec Św.
 tel.: 41 26 36 811
 fax: 41 26 54 443

Prąd rozładowania w [A] do 1,75 V/ogniwo										Prąd rozładowania w [A] do 1,70 V/ogniwo								
Typ	5'	10'	20'	30'	1 h	3h	5h	8h	10h	5'	10'	20'	30'	1 h	3h	5h	8h	10h
A502/10S	35,00	26,00	17,00	12,30	6,90	3,00	1,90	1,25	1,02	37,00	27,00	17,00	12,60	7,00	3,00	1,90	1,25	1,02
A504/3,5S	11,30	7,90	5,10	3,80	2,30	0,99	0,62	0,41	0,34	12,10	8,30	5,20	3,90	2,30	1,00	0,63	0,41	0,34
A506/1,2S	4,12	2,82	1,74	1,30	0,78	0,35	0,22	0,13	0,10	4,32	2,91	1,77	1,31	0,79	0,35	0,22	0,13	0,10
A506/3,5S	11,30	7,90	5,10	3,80	2,30	0,99	0,62	0,41	0,34	12,10	8,30	5,20	3,90	2,30	1,00	0,63	0,41	0,34
A506/4,2S	13,30	6,90	4,54	3,50	2,40	1,25	0,78	0,50	0,41	14,20	7,00	4,50	3,50	2,50	1,26	0,79	0,50	0,41
A506/6,5S	20,00	14,00	9,20	6,80	3,90	1,60	1,10	0,76	0,63	21,00	15,00	9,50	6,90	3,90	1,60	1,10	0,76	0,63
A506/10S	35,00	26,00	17,00	12,30	6,90	3,00	1,90	1,25	1,02	37,00	27,00	17,00	12,60	7,00	3,00	1,90	1,25	1,02
A508/3,5S	11,30	7,90	5,10	3,80	2,30	0,99	0,62	0,41	0,34	12,10	8,30	5,20	3,90	2,30	1,00	0,63	0,41	0,34
A512/1,2S	4,12	2,82	1,74	1,30	0,78	0,35	0,22	0,13	0,10	4,32	2,91	1,77	1,31	0,79	0,35	0,22	0,13	0,10
A512/2S	6,80	4,60	2,90	2,20	1,50	0,59	0,36	0,24	0,19	7,40	4,80	3,00	2,20	1,50	0,60	0,37	0,24	0,19
A512/3,5S	11,30	7,90	5,10	3,80	2,30	0,99	0,62	0,41	0,34	12,10	8,30	5,20	3,90	2,30	1,00	0,63	0,41	0,34
A512/6,5S	20,00	14,00	9,20	6,80	3,90	1,60	1,10	0,76	0,63	21,00	15,00	9,50	6,90	3,90	1,60	1,10	0,76	0,63
A512/10S	35,00	26,00	17,00	12,30	6,90	3,00	1,90	1,25	1,02	37,00	27,00	17,00	12,60	7,00	3,00	1,90	1,25	1,02
A512/16G5	51,0	36,0	23,0	17,0	10,4	4,5	2,9	1,8	1,5	54,0	39,0	24,0	17,0	10,5	4,6	2,9	1,8	1,5
A512/25G5	54,2	41,4	28,6	21,9	14,2	6,1	4,0	2,7	2,2	61,7	43,3	29,6	22,4	14,4	6,2	4,1	2,7	2,2
A512/30G6	84,7	60,3	42,0	31,3	19,7	8,1	5,2	3,4	2,8	92,0	64,3	43,3	32,0	20,0	8,2	5,3	3,4	2,8
A512/40A	103,0	74,0	50,0	37,0	24,0	9,4	6,8	4,5	3,7	115,0	79,0	52,0	38,0	24,0	9,5	6,8	4,5	3,7
A512/40G6	103,0	74,0	50,0	37,0	24,0	9,4	6,8	4,5	3,7	115,0	79,0	52,0	38,0	24,0	9,5	6,8	4,5	3,7
A512/55A	139,7	99,0	69,5	52,5	35,0	14,2	9,3	6,2	5,1	151,6	106,7	72,0	53,9	35,5	14,3	9,3	6,2	5,1
A512/60A	168,0	118,1	80,4	60,5	36,4	16,1	10,4	6,9	5,6	178,3	125,2	82,6	61,6	36,9	16,2	10,4	6,9	5,6
A512/60G6	168,0	118,1	80,4	60,5	36,4	16,1	10,4	6,9	5,6	178,3	125,2	82,6	61,6	36,9	16,2	10,4	6,9	5,6
A512/65A	140,6	111,3	81,9	63,8	40,0	17,8	11,7	7,6	6,3	158,3	121,3	86,2	65,9	40,6	17,9	11,7	7,6	6,3
A512/65G6	140,6	111,3	81,9	63,8	40,0	17,8	11,7	7,6	6,3	158,3	121,3	86,2	65,9	40,6	17,9	11,7	7,6	6,3
A512/85A	226,0	169,0	120,0	90,0	58,0	23,0	15,0	9,9	8,1	244,0	182,0	125,0	93,0	59,0	23,0	15,1	9,9	8,1
A512/115A	282,0	204,0	148,0	112,0	66,0	28,0	19,0	13,0	10,5	310,0	215,0	153,0	114,0	67,0	28,0	19,0	13,0	10,5
A512/120A	330,0	235,0	155,0	116,0	71,6	29,5	19,0	12,6	10,5	367,0	249,0	161,0	119,0	73,1	29,9	19,2	12,8	10,5
A512/140A	357,0	264,0	176,0	133,0	82,3	34,5	22,3	14,8	12,2	397,0	282,0	183,0	137,0	84,1	35,1	22,6	15,0	12,2
A512/200A	437,0	349,0	237,0	183,0	115,0	49,7	32,3	21,5	17,7	486,0	380,0	251,0	191,0	117,0	50,6	32,8	21,8	17,7

Prąd rozładowania w [A] do 1,65 V/ogniwo										Prąd rozładowania w [A] do 1,60 V/ogniwo								
Typ	5'	10'	20'	30'	1 h	3h	5h	8h	10h	5'	10'	20'	30'	1 h	3h	5h	8h	10h
A502/10S	39,00	28,00	17,00	12,70	7,10	3,00	1,90	1,25	1,02	42,00	29,00	17,00	12,80	7,10	3,00	1,90	1,25	1,02
A504/3,5S	12,70	8,50	5,30	3,90	2,30	1,01	0,63	0,41	0,34	13,10	8,70	5,30	3,90	2,30	1,01	0,63	0,41	0,34
A506/1,2S	4,52	2,96	1,79	1,32	0,80	0,36	0,22	0,13	0,10	4,66	3,00	1,80	1,33	0,80	0,36	0,22	0,13	0,10
A506/3,5S	12,70	8,50	5,30	3,90	2,30	1,01	0,63	0,41	0,34	13,10	8,70	5,30	3,90	2,30	1,01	0,63	0,41	0,34
A506/4,2S	14,80	7,00	4,50	3,50	2,50	1,27	0,79	0,50	0,41	15,20	7,00	4,50	3,50	2,50	1,27	0,79	0,50	0,41
A506/6,5S	23,00	15,00	9,60	7,00	4,00	1,60	1,10	0,76	0,63	24,00	16,00	9,70	7,00	4,00	1,60	1,10	0,76	0,63
A506/10S	39,00	28,00	17,00	12,70	7,10	3,00	1,90	1,25	1,02	42,00	29,00	17,00	12,80	7,10	3,00	1,90	1,25	1,02
A508/3,5S	12,70	8,50	5,30	3,90	2,30	1,01	0,63	0,41	0,34	13,10	8,70	5,30	3,90	2,30	1,01	0,63	0,41	0,34
A512/1,2S	4,52	2,96	1,79	1,32	0,80	0,36	0,22	0,13	0,10	4,66	3,00	1,80	1,33	0,80	0,36	0,22	0,13	0,10
A512/2S	7,80	4,90	3,00	2,20	1,50	0,60	0,37	0,24	0,19	8,20	5,00	3,10	2,20	1,50	0,60	0,37	0,24	0,19
A512/3,5S	12,70	8,50	5,30	3,90	2,30	1,01	0,63	0,41	0,34	13,10	8,70	5,30	3,90	2,30	1,01	0,63	0,41	0,34
A512/6,5S	23,00	15,00	9,60	7,00	4,00	1,60	1,10	0,76	0,63	24,00	16,00	9,70	7,00	4,00	1,60	1,10	0,76	0,63
A512/10S	39,00	28,00	17,00	12,70	7,10	3,00	1,90	1,25	1,02	42,00	29,00	17,00	12,80	7,10	3,00	1,90	1,25	1,02
A512/16G5	58,0	41,0	24,0	18,0	10,6	4,6	2,9	1,8	1,5	61,0	42,0	25,0	18,0	10,7	4,6	2,9	1,8	1,5
A512/25G5	67,5	45,4	30,2	22,7	14,4	6,2	4,1	2,7	2,2	71,8	46,9	30,7	22,9	14,5	6,2	4,1	2,7	2,2
A512/30G6	98,9	67,0	44,0	32,4	20,1	8,2	5,3	3,4	2,8	105,1	68,7	44,4	32,6	20,1	8,2	5,3	3,4	2,8
A512/40A	121,0	82,0	53,0	39,0	24,0	9,5	6,8	4,5	3,7	127,0	85,0	54,0	39,0	24,0	9,5	6,8	4,5	3,7
A512/40G6	121,0	82,0	53,0	39,0	24,0	9,5	6,8	4,5	3,7	127,0	85,0	54,0	39,0	24,0	9,5	6,8	4,5	3,7
A512/55A	161,2	112,3	73,6	54,7	35,7	14,4	9,3	6,2	5,1	169,8	116,2	74,6	55,2	35,8	14,4	9,3	6,2	5,1
A512/60A	185,2	130,3	83,2	61,7	37,1	16,2	10,4	6,9	5,6	191,0	133,3	83,5	61,8	37,2	16,2	10,4	6,9	5,6
A512/60G6	185,2	130,3	83,2	61,7	37,1	16,2	10,4	6,9	5,6	191,0	133,3	83,5	61,8	37,2	16,2	10,4	6,9	5,6
A512/65A	178,5	129,8	88,8	67,0	40,9	17,9	11,7	7,6	6,3	193,1	135,7	90,3	67,7	41,1	18,0	11,7	7,6	6,3
A512/65G6	178,5	129,8	88,8	67,0	40,9	17,9	11,7	7,6	6,3	193,1	135,7	90,3	67,7	41,1	18,0	11,7	7,6	6,3
A512/85A	259,0	192,0	128,0	94,0	59,0	24,0	15,1	9,9	8,1	273,0	199,0	130,0	95,0	60,0	23,0	15,1	9,9	8,1
A512/115A	332,0	222,0	156,0	116,0	67,0	28,0	19,0	13,0	10,5	343,0	227,0	158,0	117,0	68,0	28,0	19,0	13,0	10,5
A512/120A	387,0	260,0	165,0	122,0	74,0	30,1	18,0	11,3	9,0	409,0	267,0	168,0	124,0	74,7	30,2	18,1	11,3	9,0
A512/140A	423,0	294,0	189,0	141,0	85,4	35,4	21,2	13,3	10,6	452,0	303,0	193,0	143,0	86,3	35,3	21,2	13,3	10,6
A512/200A	531,0	395,0	262,0	198,0	120,0	51,0	30,6	19,1	15,3	581,0	411,0	269,0	202,0	121,0	51,1	30,6	19,1	15,3



Tabela rozładowań stałą mocą A500 dla 20°C

Moc rozładowania w [W/blok] do 1,85 V/og,										Moc rozładowania w [W/blok] do 1,80 V/og,								
Typ	3'	5'	10'	15'	20'	30'	45'	60'	90'	3'	5'	10'	15'	20'	30'	45'	60'	90'
A502/10S	56,0	50,0	41,0	33,0	27,0	20,0	16,0	13,0	9,0	56,0	53,0	44,0	35,0	29,0	21,0	17,0	14,0	10,0
A504/3,5S	41,0	34,0	26,0	21,0	17,0	13,0	11,0	9,0	6,0	45,0	38,0	28,0	22,0	19,0	14,0	11,0	9,0	6,0
A506/1,2S	21,4	17,2	12,2	10,3	8,6	6,6	4,9	4,0	3,0	23,5	19,1	13,3	10,9	9,1	6,9	5,1	4,1	3,0
A506/3,5S	62,0	51,0	38,0	32,0	26,0	20,0	16,0	13,0	9,0	68,0	57,0	42,0	33,0	28,0	21,0	17,0	13,0	10,0
A506/4,2S	77,0	63,0	44,0	35,0	30,0	23,0	16,0	14,0	11,0	83,0	71,0	49,0	39,0	35,0	31,0	17,0	14,0	11,0
A506/6,5S	120,0	100,0	73,0	60,0	51,0	38,0	28,0	23,0	16,0	128,0	112,0	80,0	63,0	54,0	40,0	30,0	24,0	17,0
A506/10S	167,0	149,0	124,0	98,0	80,0	60,0	49,0	39,0	28,0	168,0	159,0	131,0	104,0	86,0	64,0	51,0	41,0	29,0
A508/3,5S	83,0	68,0	51,0	42,0	35,0	27,0	22,0	17,0	12,0	91,0	76,0	56,0	44,0	37,0	28,0	23,0	18,0	13,0
A512/1,2S	42,7	34,4	24,3	20,7	17,2	13,2	9,8	8,0	5,9	47,0	38,3	26,5	21,7	18,1	13,7	10,2	8,2	6,0
A512/2S	74,0	60,0	44,0	36,0	30,0	23,0	17,0	14,0	10,0	83,0	68,0	49,0	38,0	32,0	24,0	18,0	15,0	11,0
A512/3,5S	124,0	102,0	77,0	63,0	52,0	40,0	33,0	26,0	18,0	136,0	114,0	84,0	66,0	56,0	42,0	34,0	27,0	19,0
A512/6,5S	240,0	200,0	146,0	120,0	102,0	76,0	56,0	46,0	32,0	256,0	224,0	160,0	126,0	108,0	80,0	60,0	48,0	34,0
A512/10S	335,0	298,0	248,0	195,0	160,0	120,0	98,0	78,0	56,0	336,0	318,0	261,0	209,0	172,0	128,0	101,0	81,0	59,0
A512/16G5	485,0	433,0	352,0	295,0	252,0	192,0	150,0	119,0	87,0	584,0	485,0	384,0	309,0	269,0	203,0	156,0	124,0	90,0
A512/25G5	535,0	463,0	387,0	324,0	278,0	225,0	170,0	140,0	105,0	623,0	555,0	418,0	360,0	303,0	240,0	180,0	146,0	109,0
A512/30G6	857,0	751,0	568,0	479,0	400,0	310,0	251,0	200,0	144,0	1036	850,0	637,0	517,0	433,0	330,0	264,0	210,0	151,0
A512/40A	958,0	848,0	703,0	578,0	490,0	395,0	300,0	243,0	178,0	1092	1007	758,0	646,0	538,0	415,0	318,0	255,0	186,0
A512/40G6	958,0	848,0	703,0	578,0	490,0	395,0	300,0	243,0	178,0	1092	1007	758,0	646,0	538,0	415,0	318,0	255,0	186,0
A512/55A	1348	1172	922,0	844,0	718,0	572,0	457,0	367,0	269,0	1555	1362	1014	888,0	777,0	606,0	478,0	382,0	278,0
A512/60A	1618	1414	1096	963,0	807,0	625,0	459,0	369,0	271,0	1955	1634	1181	1041	873,0	669,0	489,0	390,0	283,0
A512/60G6	1618	1414	1096	963,0	807,0	625,0	459,0	369,0	271,0	1955	1634	1181	1041	873,0	669,0	489,0	390,0	283,0
A512/65A	1180	1113	991,0	861,0	763,0	659,0	500,0	411,0	307,0	1459	1316	1109	989,0	851,0	693,0	544,0	441,0	327,0
A512/65G6	1180	1113	991,0	861,0	763,0	659,0	500,0	411,0	307,0	1459	1316	1109	989,0	851,0	693,0	544,0	441,0	327,0
A512/85A	1979	1802	1527	1310	1118	905,0	690,0	565,0	425,0	2279	2132	1684	1487	1245	970,0	740,0	600,0	447,0
A512/115A	2808	2531	2009	1705	1439	1155	872,0	702,0	512,0	3189	2873	2190	1888	1569	1209	926,0	739,0	535,0
A512/120A	3350	2862	2300	1895	1583	1200	938,0	757,0	583,0	3763	3276	2543	2027	1720	1285	966,0	794,0	608,0
A512/140A	3674	3172	2549	2101	1755	1330	1040	839,0	647,0	4127	3631	2819	2246	1906	1424	1070	880,0	674,0
A512/200A	4690	4102	3449	2843	2375	1800	1408	1135	875,0	5268	4695	3815	3040	2580	1928	1449	1191	912,0

ETC Plus SA
 ul. Drukarska 14
 27-400 Ostrowiec Św.
 tel.: 41 26 36 811
 fax: 41 26 54 443

Moc rozładowania w [W/blok] do 1,75 V/og,										Moc rozładowania w [W/blok] do 1,70 V/og,								
Typ	3'	5'	10'	15'	20'	30'	45'	60'	90'	3'	5'	10'	15'	20'	30'	45'	60'	90'
A502/10S	60,0	58,0	45,0	36,0	30,0	22,0	17,0	14,0	10,0	64,0	60,0	46,0	38,0	31,0	22,0	17,0	14,0	10,0
A504/3,5S	49,0	41,0	30,0	23,0	20,0	15,0	12,0	9,0	6,0	53,0	44,0	31,0	24,0	20,0	15,0	12,0	9,0	7,0
A506/1,2S	25,1	20,7	14,0	11,1	9,3	7,0	5,2	4,2	3,0	26,8	21,9	14,4	11,2	9,4	7,1	5,2	4,2	3,1
A506/3,5S	73,0	62,0	45,0	35,0	29,0	22,0	18,0	14,0	10,0	80,0	66,0	46,0	36,0	30,0	22,0	18,0	14,0	10,0
A506/4,2S	89,0	77,0	52,0	40,0	36,0	31,0	17,0	15,0	11,0	97,0	81,0	54,0	41,0	36,0	32,0	17,0	15,0	11,0
A506/6,5S	138,0	121,0	86,0	66,0	57,0	42,0	30,0	24,0	17,0	150,0	126,0	88,0	68,0	58,0	42,0	31,0	24,0	17,0
A506/10S	181,0	173,0	135,0	109,0	90,0	66,0	51,0	42,0	30,0	193,0	180,0	139,0	113,0	92,0	67,0	52,0	42,0	30,0
A508/3,5S	97,0	82,0	60,0	46,0	39,0	29,0	23,0	18,0	13,0	106,0	88,0	61,0	48,0	40,0	30,0	24,0	19,0	13,0
A512/1,2S	50,1	41,4	28,0	22,2	18,6	14,0	10,3	8,3	6,1	53,7	43,7	28,8	22,4	18,8	14,1	10,4	8,4	6,1
A512/2S	91,0	75,0	52,0	40,0	33,0	25,0	18,0	15,0	11,0	99,0	80,0	53,0	41,0	34,0	25,0	19,0	15,0	11,0
A512/3,5S	146,0	123,0	89,0	69,0	59,0	44,0	35,0	27,0	19,0	159,0	131,0	92,0	72,0	60,0	45,0	35,0	28,0	20,0
A512/6,5S	276,0	242,0	172,0	132,0	114,0	84,0	60,0	48,0	34,0	300,0	252,0	176,0	136,0	116,0	84,0	62,0	48,0	34,0
A512/10S	361,0	346,0	270,0	219,0	179,0	132,0	103,0	83,0	60,0	385,0	360,0	278,0	226,0	185,0	135,0	103,0	84,0	60,0
A512/16G5	636,0	534,0	407,0	322,0	280,0	209,0	159,0	126,0	91,0	688,0	573,0	418,0	331,0	285,0	212,0	161,0	127,0	91,0
A512/25G5	689,0	616,0	454,0	385,0	320,0	248,0	185,0	150,0	111,0	776,0	652,0	482,0	395,0	330,0	253,0	187,0	151,0	112,0
A512/30G6	1118	951,0	690,0	538,0	453,0	341,0	271,0	214,0	153,0	1214	1037	726,0	558,0	465,0	347,0	274,0	216,0	155,0
A512/40A	1226	1074	822,0	691,0	569,0	432,0	326,0	261,0	189,0	1391	1157	870,0	719,0	587,0	441,0	331,0	264,0	191,0
A512/40G6	1226	1074	822,0	691,0	569,0	432,0	326,0	261,0	189,0	1391	1157	870,0	719,0	587,0	441,0	331,0	264,0	191,0
A512/55A	1799	1496	1102	917,0	813,0	626,0	489,0	388,0	281,0	1912	1624	1163	935,0	834,0	636,0	493,0	392,0	283,0
A512/60A	2267	1837	1274	1071	915,0	693,0	505,0	400,0	288,0	2406	2022	1348	1088	940,0	707,0	514,0	405,0	290,0
A512/60G6	2267	1837	1274	1071	915,0	693,0	505,0	400,0	288,0	2406	2022	1348	1088	940,0	707,0	514,0	405,0	290,0
A512/65A	1757	1591	1223	1083	914,0	721,0	567,0	457,0	336,0	1959	1739	1322	1142	954,0	739,0	577,0	464,0	340,0
A512/65G6	1757	1591	1223	1083	914,0	721,0	567,0	457,0	336,0	1959	1739	1322	1142	954,0	739,0	577,0	464,0	340,0
A512/85A	2561	2292	1847	1557	1329	1018	768,0	621,0	460,0	2900	2486	1993	1607	1381	1045	786,0	634,0	469,0
A512/115A	3642	3101	2374	1986	1653	1255	956,0	759,0	547,0	4106	3361	2511	2030	1703	1281	971,0	770,0	553,0
A512/120A	4237	3552	2627	2134	1800	1334	989,0	815,0	622,0	4536	3800	2690	2201	1849	1365	1008	830,0	632,0
A512/140A	4647	3937	2912	2365	1995	1479	1096	904,0	689,0	4974	4211	2981	2440	2050	1513	1117	920,0	700,0
A512/200A	5932	5092	3941	3201	2700	2002	1484	1223	933,0	6350	5446	4034	3302	2774	2048	1512	1245	948,0

Moc rozładowania w [W/blok] do 1,65 V/og,										Moc rozładowania w [W/blok] do 1,60 V/og,								
Typ	3'	5'	10'	15'	20'	30'	45'	60'	90'	3'	5'	10'	15'	20'	30'	45'	60'	90'
A502/10S	68,0	62,0	47,0	38,0	31,0	23,0	17,0	14,0	10,0	73,0	63,0	48,0	38,0	31,0	23,0	17,0	14,0	10,0
A504/3,5S	57,0	46,0	31,0	24,0	20,0	15,0	12,0	9,0	7,0	59,0	46,0	32,0	25,0	20,0	15,0	12,0	9,0	7,0
A506/1,2S	28,2	22,6	14,7	11,2	9,5	7,1	5,2	4,2	3,1	29,2	23,1	14,8	11,3	9,5	7,1	5,2	4,2	3,1
A506/3,5S	85,0	68,0	47,0	36,0	30,0	23,0	18,0	14,0	10,0	89,0	69,0	47,0	37,0	31,0	23,0	18,0	14,0	10,0
A506/4,2S	102,0	82,0	55,0	41,0	36,0	32,0	17,0	15,0	11,0	106,0	83,0	55,0	42,0	37,0	32,0	17,0	15,0	11,0
A506/6,5S	160,0	129,0	90,0	69,0	59,0	43,0	31,0	25,0	18,0	168,0	132,0	92,0	70,0	59,0	43,0	31,0	25,0	18,0
A506/10S	205,0	186,0	142,0	114,0	93,0	68,0	52,0	42,0	30,0	218,0	190,0	144,0	115,0	94,0	68,0	52,0	42,0	30,0
A508/3,5S	113,0	91,0	62,0	49,0	41,0	30,0	24,0	19,0	13,0	119,0	93,0	63,0	49,0	41,0	30,0	24,0	19,0	13,0
A512/1,2S	56,4	45,3	29,4	22,5	18,9	14,2	10,5	8,4	6,1	58,4	46,2	29,7	22,5	19,0	14,2	10,5	8,4	6,2
A512/2S	103,0	82,0	54,0	41,0	34,0	25,0	19,0	15,0	11,0	106,0	84,0	55,0	42,0	34,0	25,0	19,0	15,0	11,0
A512/3,5S	170,0	137,0	93,0	73,0	61,0	45,0	35,0	28,0	20,0	178,0	139,0	95,0	74,0	61,0	45,0	36,0	28,0	20,0
A512/6,5S	320,0	258,0	180,0	138,0	118,0	86,0	62,0	50,0	36,0	336,0	264,0	184,0	140,0	118,0	86,0	62,0	50,0	36,0
A512/10S	410,0	371,0	283,0	229,0	187,0	136,0	104,0	84,0	61,0	437,0	381,0	287,0	231,0	188,0	136,0	104,0	85,0	61,0
A512/16G5	741,0	601,0	423,0	335,0	288,0	213,0	161,0	128,0	92,0	783,0	621,0	426,0	338,0	289,0	214,0	162,0	128,0	92,0
A512/25G5	854,0	693,0	501,0	400,0	335,0	255,0	188,0	152,0	112,0	908,0	725,0	514,0	403,0	339,0	256,0	189,0	153,0	113,0
A512/30G6	1310	1095	746,0	569,0	471,0	351,0	276,0	217,0	155,0	1393	1121	755,0	576,0	474,0	352,0	276,0	218,0	156,0
A512/40A	1514	1235	902,0	729,0	597,0	446,0	333,0	265,0	192,0	1577	1299	923,0	735,0	603,0	449,0	334,0	266,0	192,0
A512/40G6	1514	1235	902,0	729,0	597,0	446,0	333,0	265,0	192,0	1577	1299	923,0	735,0	603,0	449,0	334,0	266,0	192,0
A512/55A	2005	1726	1204	945,0	845,0	642,0	496,0	394,0	284,0	2107	1800	1231	957,0	851,0	645,0	498,0	395,0	285,0
A512/60A	2548	2176	1404	1098	954,0	715,0	519,0	409,0	292,0	2680	2279	1439	1104	963,0	719,0	522,0	410,0	293,0
A512/60G6	2548	2176	1404	1098	954,0	715,0	519,0	409,0	292,0	2680	2279	1439	1104	963,0	719,0	522,0	410,0	293,0
A512/65A	2139	1853	1395	1171	976,0	749,0	582,0	466,0	341,0	2315	1976	1443	1183	987,0	754,0	584,0	468,0	342,0
A512/65G6	2139	1853	1395	1171	976,0	749,0	582,0	466,0	341,0	2315	1976	1443	1183	987,0	754,0	584,0	468,0	342,0
A512/85A	3115	2719	2109	1663	1410	1060	797,0	642,0	474,0	3264	2923	2190	1700	1427	1069	804,0	648,0	477,0
A512/115A	4304	3582	2603	2057	1732	1296	980,0	776,0	557,0	4467	3755	2665	2073	1750	1306	985,0	780,0	560,0
A512/120A	4847	4002	2761	2246	1883	1387	1022	843,0	640,0	5135	4156	2812	2276	1906	1403	1032	852,0	646,0
A512/140A	5316	4435	3060	2489	2087	1538	1133	934,0	709,0	5631	4606	3117	2522	2113	1555	1144	945,0	716,0
A512/200A	6786	5736	4142	3369	2825	2081	1533	1264	959,0	7189	5957	4218	3413	2860	2104	1548	1279	969,0